

# PRODUCT DATA SHEET

## *Thompson's* uPVC RESTORER

Thompson's uPVC Restorer's unique formulation cleans, revives and whitens dirty and weathered uPVC. The powerful cleaning action removes ingrained dirt without scratching the surface.

### INTRODUCTION

Thompson's uPVC Restorer is a specially formulated cleaner which is designed to transform dirty and weathered uPVC, back to white. The powerful surfactants remove ingrained dirt without scratching the surface.

Thompson's uPVC Restorer is guaranteed to leave uPVC surfaces clean and bright every time. It's water based formulation makes it safe and easy to use.

### COMPOSITION

A blend of petroleum distillates, solvents and surfactants with fillers and viscosity modifiers.

### PROPERTIES

Appearance – Off-white/cream viscous liquid.  
VOC Content – Medium ( 8-24.99% w/v).  
Odour- Low, inoffensive.  
Solubility – Forms an emulsion with water.

### FIELDS OF APPLICATION

Thompson's uPVC Restorer is suitable for use on white uPVC (PVCu) surfaces such as doors, windows, cladding, fascias, guttering, conservatories and greenhouse frames.

### PREPARATION

Wipe off any surface debris using a wet cloth or sponge prior to application.

### APPLICATION

Shake well before use. Pour uPVC Restorer onto a dampened cloth and work into the surface. Apply one section of a window frame (or one panel of a door) at a time, then buff off using a dry cloth. Repeat on individual sections until job is complete.

Try to avoid working in direct sunlight as this will cause the product to dry too quickly, making it more difficult to buff off. If working in direct sunlight apply to a limited area and buff immediately. Thompson's uPVC Restorer is guaranteed to remove dirt and surface staining caused by natural weathering. It is not guaranteed to remove dirt or marks from damaged, chipped or scratched uPVC surfaces.

### IMPORTANT NOTES

Refer to instructions on the pack before use.

If spilled onto windows, wipe off with a damp cloth.

If spilled onto brickwork brush down with warm water and detergent.

In some original or early uPVC, yellowing may extend below the surface of the uPVC. In these cases Thompson's uPVC Restorer will reduce yellowing, but will not return the uPVC back to white.

Store in frost free conditions.

### HEALTH & SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health & safety sheets are available upon request.

### STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition.

Ensure container is fully re-sealed after use.

To avoid the risk of spillage always store and transport in a secure and upright position.

### FLAMMABILITY

Non-flammable product.

### SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

### SIZES

Available in a 480ml resealable container.

### DISPOSAL

Some local authorities have special facilities for disposal of waste products.

Dispose of in accordance with Local Authority requirements.

Do not empty product into drains or watercourses.

## LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

## INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

## DATA SHEETS

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

**Sherwin-Williams Diversified Brands Ltd**  
**Thornccliffe Park**  
**Chapelton**  
**Sheffield**  
**S35 2YP**

Tel: +44(0)114 246 7171  
Fax: +44(0)114 245 5629

*Registered in England 2968830*

E. Mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)  
Website: [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

MAY, 2017. ISSUE 2