



## DECLARATION OF PERFORMANCE

1. **Factory Control Certificate Number:** 0013-CPD-537588

2. **Product Group:**

**Type A** – Polymeric / DPC Sheets

3. **Unique Product Names / Codes:**

Product Name	Unique Identification Code	Thickness	Nominal Dimensions
Hyload Original	31599900	1.25mm	20m x various widths
Hyload Mortar Match (White)	30599900	1.27mm	20m x various widths
Hyload Mortar Match (Brown)	32599900	1.27mm	20m x various widths
Hyload Trade	31699900	0.9mm	20m x various widths
Hyload Permabit	34599900	1.25mm	20m x various widths

4. **Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Linear damp proof course (DPC), bonded at joints.

5. **Manufacturer:**

IKO PLC  
Appley Lane North  
Appley Bridge  
Wigan  
Lancashire  
WN6 9AB

6. **Authorised Representative:** Not applicable

7. **System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR**

3 +

8. **Harmonised standard:** EN 14967:2006

9. **Notified Body:** BSI-08

## 10. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Watertightness	2kPA for 24 hrs	EN 1928
Maximum tensile force	≥ 3 Mpa	EN 12311-1
Elongation	≥ 110%	EN 12311-1
Resistance to static loading	20kg (concrete) 5kg (EPS)	EN 12730 (B)
Resistance to impact	500mm (Aluminium) 150mm (EPS)	EN 12691
Resistance to tearing	Long ≥ 8.63N/mm	EN 12310-1
Flexibility at low temperature	-15	EN 1109
Durability (ageing)	Pass	EN 1296
Durability (alkali)	Pass	ANNEX C

Signed for and on behalf of the manufacturer by:



Terry Edwards  
Development Manager

**Date:** 11<sup>th</sup> April 2018